IARJSET ISSN (O) 2393-8021, ISSN (P) 2394-1588

International Advanced Research Journal in Science, Engineering and Technology

Impact Factor 8.311 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 13, Issue 11, November 2026

DOI: 10.17148/IARJSET.2026.131174

Future of Biofuels from Agricultural Waste Challenges, Opportunities, and Improvement Strategies

Maroof N E[1], Hashim A S[2], Femi Philomina Francis[3]

Workshop Superintendent, Department of Mechanical Engineering, Seethi Sahib Memorial Polytechnic College, Tirur, Kerala, India[1]

Lecturer in Mechanical Engineering, Seethi Sahib Memorial Polytechnic College, Tirur, Kerala, India[2]

Junior Instructor, Government ITI, Kalamassery, Kerala, India[3]

Abstract: Crop residues such as rice and wheat straw, maize stover, sugarcane bagasse and coconut husk are among the largest underused renewable resources in India, where roughly 500 million tonnes of agricultural biomass are generated each year and a large share is burned in the field or left to rot. This review examines how second-generation biofuels (cellulosic ethanol, biogas, bio-oil and syngas, and biodiesel from oilseed residues) can turn that waste into fuel. Drawing on published resource assessments and on indicative yield, energy, emission and cost figures compiled by the authors, it outlines the scale of the opportunity, points out where optimistic estimates diverge from what operating plants have delivered, and discusses the main barriers: scattered and seasonal feedstock, costly pretreatment and enzymes, high capital cost and weak rural infrastructure. Seven improvement strategies are then proposed: advanced pretreatment, better enzymes and microbes, integrated biorefineries, farm-scale processing, stronger supply chains, supportive policy and continued research. The analysis suggests that residue-based biofuels can contribute meaningfully to energy security, rural income and emission reduction, provided that feedstock logistics and process economics are tackled together. IndexTerms - Agricultural waste, biofuels, biomass, cellulosic ethanol, biogas, bioenergy, sustainability, energy security.

I. INTRODUCTION

Energy demand keeps climbing with population, industry and rising living standards, and most of it is still met by coal, oil and natural gas. These fuels are finite, and burning them drives air pollution and climate change. For countries such as India, which import most of their crude oil, they also carry a heavy import bill. Renewable fuels made from biological material offer one way of loosening that dependence [1].

Biofuels first entered the mainstream as products of food crops: ethanol from sugarcane and maize, biodiesel from vegetable oils. Using farmland and food for fuel, however, set energy against nutrition and prices, and attention has since shifted to second-generation biofuels made from non-food biomass, chiefly the straws, husks, stalks and shells that remain after crops are harvested and processed [2].

India alone generates something like 500 million tonnes of such residue every year. Much of it is burned in open fields, which fouls the air in the post-harvest season, or is left to decompose, which releases methane and wastes a resource. This paper reviews the future of fuels made from this material. It describes the feedstocks and conversion routes, summarises the potential and indicative performance of the main fuels, sets out the technical, economic and logistical barriers, and proposes strategies that could make residue-based biofuels commercially and environmentally viable. Where figures are estimates compiled by the authors they are labelled as such, and where operating plants have delivered less than laboratory yields suggest, this is stated plainly.

II. AGRICULTURAL RESIDUES AS FEEDSTOCK

A. Types of residue

Residues fall into two groups according to where they arise (Table 1). Field residues stay on the land after harvest, while processing residues come out of mills and agro-industries and are therefore already concentrated at one site, which makes them easier to collect. Both groups are lignocellulosic: their dry mass is mostly cellulose, hemicellulose and lignin, the three polymers that give plant cell walls their strength [3]. Cellulose and hemicellulose can be broken down to sugars and then fuel, whereas lignin resists biological conversion and is better used as a source of heat or chemicals.

© IARJSET This work is licensed under a Creative Commons Attribution 4.0 International License

IARJSET ISSN (O) 2393-8021, ISSN (P) 2394-1588

International Advanced Research Journal in Science, Engineering and Technology

Impact Factor 8.311 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 13, Issue 11, November 2026

DOI: 10.17148/IARJSET.2026.131174

TABLE I MAIN GROUPS OF AGRICULTURAL RESIDUE USED AS BIOFUEL FEEDSTOCK.

Group	Examples
Field residues	Rice straw, wheat straw, maize (corn) stover, cotton stalk, sugarcane leaves
Processing residues	Sugarcane bagasse, rice husk, coconut shell, groundnut shell, oilseed cake

B. Availability in India

Published estimates of residue availability differ with the year, the crops counted and the definition of "surplus". A national assessment by the Ministry of New and Renewable Energy (MNRE) and the Indian Institute of Science put annual generation of agricultural and agro-industrial residue at about 511 million tonnes, of which 120–150 million tonnes could be spared for energy [6]. An independent study reported 480 million tonnes gross and 121 million tonnes surplus [8], and the more recent National Biomass Atlas gives about 228.5 million tonnes of surplus residue [7]. The crop-wise figures compiled for this study are listed in Table 2 and plotted in Fig. 1. Rice and wheat straw dominate, together making up roughly two-thirds of the headline total of 500–550 million tonnes a year.

TABLE II INDICATIVE CROP PRODUCTION AND RESIDUE GENERATION IN INDIA (AUTHOR-COMPILED).

Crop	Annual production (Mt)	Residue generated (Mt/year)
Rice	130	180–200
Wheat	110	160–170
Sugarcane	400	120–140 (bagasse + trash)
Maize	35	45–50
Cotton	30	50–60
Other crops	—	80–100
Sum of the rows above	**—**	**635–720**

Mt = million tonnes. The row sum is calculated here; the headline total used in the text is 500–550 Mt/year.

The rows in Table 2 add up to 635–720 million tonnes, more than the 500–550 million tonnes usually quoted for India and more than the 480–511 million tonnes in the assessments cited above [6], [8]. The gap most likely reflects residue-to-product ratios applied to peak-year output, and some overlap between categories. The crop-wise figures are therefore best read as upper bounds, and the rest of this paper works from the more conservative headline figure. The authors also estimate that 35–40% of the biomass is burned or otherwise wasted today; this share is not taken from a cited survey and is indicative only.




Fig. 1 Residue generated per year by crop, as ranges (Table 2). The rows sum to more than the national headline figure, so they are treated as upper bounds.

© IARJSET This work is licensed under a Creative Commons Attribution 4.0 International License

IARJSET ISSN (O) 2393-8021, ISSN (P) 2394-1588

International Advanced Research Journal in Science, Engineering and Technology

Impact Factor 8.311 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 13, Issue 11, November 2026

DOI: 10.17148/IARJSET.2026.131174

III. CONVERSION PATHWAYS AND BIOFUEL PRODUCTS

Three families of conversion route are relevant to residues. In the biochemical route, a pretreatment step opens the tight fibre structure, enzymes then hydrolyse cellulose and hemicellulose to sugars, and yeast or bacteria ferment those sugars to ethanol. In anaerobic digestion, microbes decompose wet biomass in the absence of oxygen and release biogas, a mixture of methane and carbon dioxide that can be burned for cooking or power or upgraded to compressed biogas (CBG). Thermochemical routes use heat: pyrolysis yields a liquid bio-oil and gasification yields a combustible syngas, both usable for heat and electricity. Oilseed cakes, finally, retain some residual oil that can be converted to biodiesel. Table 3 matches feedstocks with fuels and end uses.

TABLE III AGRICULTURAL RESIDUES, THE BIOFUELS THEY CAN YIELD AND TYPICAL END USES.

Agricultural waste	Biofuel	End use
Rice straw, wheat straw	Cellulosic ethanol	Transport fuel
Sugarcane bagasse	Ethanol, biogas	Vehicles, electricity
Cow dung with crop waste	Biogas	Cooking, power
Rice husk, nut shells	Bio-oil, syngas	Heat, electricity
Oilseed cakes	Biodiesel	Diesel engines

IV. POTENTIAL AND INDICATIVE PERFORMANCE

A. Resource scale and yields

Suppose that 30% of the 500–550 million tonnes of residue could be collected sustainably. That is about 150 million tonnes a year. Using the indicative yields in Table 4, which are the kind of values reported at laboratory or pilot scale, 150 million tonnes would correspond to roughly 38–45 billion litres of ethanol, or to 26–36 billion cubic metres of biogas. These are alternatives rather than additions, because a tonne of straw cannot be fermented and digested at the same time.

TABLE IV INDICATIVE BIOFUEL YIELDS PER TONNE OF RESIDUE (AUTHOR-COMPILED).

Biomass type	Ethanol yield (L/t)	Biogas yield (m^3/t)
Rice straw	250–280	200–220
Wheat straw	260–300	210–230
Corn stover	280–310	220–240
Sugarcane bagasse	240–270	180–200
Cotton stalk	200–230	170–190

Operating experience is less generous. India's first commercial second-generation ethanol plant, at Panipat, was designed to process about 200,000 tonnes of rice straw a year into roughly 30 million litres of ethanol [5]. That works out at about 150 litres per tonne, around half of the Table 4 values, and the plant has been reported to run below design capacity because the feedstock varies in quality [10]. Yields at commercial scale should therefore be planned conservatively until more plants have operated for several years.

The power route can be checked with a simple energy balance. Dry biomass holds 15–18 MJ/kg, so 150 million tonnes carry about 2.3–2.7 EJ a year. At an electrical conversion efficiency of 30%, this corresponds to an average output of roughly 21–26 GW. That is consistent with the 18–28 GW potential associated with the national surplus estimates [6], [7], and it suggests that figures well above this range should be treated with caution.

B. Energy content

Ethanol carries less energy per litre than the fuels it replaces (Table 5). At 21 MJ/L against 34 MJ/L for petrol, it holds about 62% of the energy, so a litre of neat ethanol gives less driving range than a litre of petrol. At the low blend levels used today the effect on a vehicle is small, but it explains why ethanol must be compared with petrol on an energy basis and not simply per litre.

© IARJSET This work is licensed under a Creative Commons Attribution 4.0 International License

IARJSET ISSN (O) 2393-8021, ISSN (P) 2394-1588

International Advanced Research Journal in Science, Engineering and Technology

Impact Factor 8.311 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 13, Issue 11, November 2026

DOI: 10.17148/IARJSET.2026.131174

TABLE V ENERGY CONTENT OF SELECTED FUELS (AUTHOR-COMPILED).

Fuel	Energy content
Diesel	36 MJ/L
Petrol	34 MJ/L
Ethanol	21 MJ/L
Biogas	20–23 MJ/m³
Biomass (dry)	15–18 MJ/kg

C. Greenhouse-gas emissions

The clearest advantage of residue-based fuels is their lower carbon intensity (Fig. 2). Taking the indicative values of 20–30 g CO_2/MJ for ethanol from crop waste and 94 g CO_2/MJ for petrol, ethanol is some 68–79% lower; biogas at 15–25 g CO_2/MJ is lower still. The authors estimate that replacing 20% of India's petrol with residue-derived ethanol could avoid about 35 million tonnes of CO_2 a year. All such figures depend on the system boundary, on how residue collection and transport are counted, and on avoided open burning, so they should be confirmed with a full life-cycle assessment before being used in policy.




Fig. 2 Indicative CO_2 emission intensity of petrol, diesel and residue-based biofuels (author-compiled). Error bars span the quoted ranges.

D. Production cost

Table 6 compares indicative 2025 production costs. Cellulosic ethanol at ₹55–65 per litre corresponds to about ₹2.6–3.1 per MJ, while petrol at ₹95–105 per litre corresponds to about ₹2.8–3.1 per MJ. On an energy basis the two are therefore roughly level, not clearly different. The petrol figure also looks closer to a retail price, with taxes, than to a production cost, so the comparison is not strictly like for like. The fair reading is that residue-based ethanol can be competitive, but whether it is cheaper depends on feedstock price, enzyme cost, plant scale and the subsidies and taxes applied.

TABLE VI INDICATIVE PRODUCTION COST OF FUELS, 2025 (AUTHOR ESTIMATE).

Fuel	Cost (₹ per litre equivalent)
Petrol	95–105
Diesel	90–100
Cellulosic ethanol	55–65
Biogas (CBG)	45–55

E. Rural employment

Biomass processing is labour-intensive in collection, baling, transport and plant operation. As an indicative planning figure, each 100,000 tonnes of biomass processed per year might support 200–300 direct and 400–500 indirect jobs and

IARJSET ISSN (O) 2393-8021, ISSN (P) 2394-1588

International Advanced Research Journal in Science, Engineering and Technology

Impact Factor 8.311 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 13, Issue 11, November 2026

DOI: 10.17148/IARJSET.2026.131174

bring ₹25–30 crore of income into rural areas. These numbers are the authors' estimates and will vary with the technology, the plant location and the local wage level.

V. MAJOR CHALLENGES

A. Collection and transport

Residues are spread thinly over large areas and have a low bulk density, so gathering and hauling them to a plant is expensive. Transport can consume a large part of the feedstock cost, and long hauls add emissions that erode the climate benefit.

B. Seasonal availability

Straw and stalks become available only after harvest. A plant that runs all year therefore needs storage or a mix of feedstocks, otherwise it faces supply gaps and idle capacity.

C. Pretreatment difficulty

Lignin locks cellulose inside the cell wall, and releasing it requires a pretreatment step that is energy-intensive, costly and, with some chemicals, polluting. Pretreatment is widely regarded as one of the main cost drivers of second-generation fuels.

D. High production cost

Enzymes, pressure vessels, fermenters and purification units make capital and operating costs high. Until plants reach reliable scale and yield, second-generation fuels depend on policy support to compete.

E. Lack of infrastructure

Many rural areas lack the storage sheds, roads and biorefinery capacity needed to handle residues in volume. Experience with biomass power shows the risk: one study reported that the average plant load factor of biomass plants fell from 46% in 2015 to 17.1% in 2019, partly because fuel was scarce and its cost rising [11]. A one-megawatt biomass plant needs on the order of 7,000–10,000 tonnes of fuel a year [11], which shows how heavily any plant depends on a dependable local supply.

VI. ENVIRONMENTAL AND SOCIAL BENEFITS

Turning residue into fuel instead of burning it brings several benefits at once:

- less open burning of stubble, and so cleaner air in the harvest season;
- lower CO_2 emissions where residue-based fuels replace petrol and diesel;
- an extra income stream for farmers who sell residue they would otherwise dispose of;
- rural jobs in collection, transport and plant operation; and
- better waste management, with digestate and other by-products returned to the land.

These gains are real but not automatic. Removing too much residue can deprive soil of organic matter, so collection rates must be set with local soil health in mind.

VII. IMPROVEMENT STRATEGIES FOR THE FUTURE

A. Advanced pretreatment

Because lignin acts as a natural glue around the cellulose, pretreatment determines how much sugar can be recovered. Conventional chemical treatments are costly and can pollute, and several alternatives are being developed. Steam explosion breaks the fibre structure with high-pressure steam. Biological pretreatment uses fungi and microbes to remove lignin slowly with little energy. Ionic liquids can dissolve lignin without damaging cellulose, and ammonia fibre expansion (AFEX) makes the cellulose more accessible to enzymes. Better pretreatment increases sugar yield, reduces enzyme use and lowers the cost of the final fuel, which is what makes cellulosic ethanol and biogas competitive.

B. Better enzymes and microorganisms

After pretreatment, enzymes turn cellulose into sugars and microbes ferment the sugars. Present enzymes are expensive and slow. Promising directions include engineered enzymes that work faster, heat-tolerant microbes that cut cooling costs, multi-enzyme systems that attack cellulose and hemicellulose together, and organisms that tolerate the impurities in real residue streams. Together these should shorten processing time, raise yield and lower operating cost.

© IARJSET This work is licensed under a Creative Commons Attribution 4.0 International License

IARJSET ISSN (O) 2393-8021, ISSN (P) 2394-1588

International Advanced Research Journal in Science, Engineering and Technology

Impact Factor 8.311 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 13, Issue 11, November 2026

DOI: 10.17148/IARJSET.2026.131174

C. Integrated biorefineries

A future plant need not make only one fuel. Like an oil refinery, a biorefinery can turn one feedstock into several products: ethanol, biogas, electricity, fertiliser, animal feed and biochemicals (Fig. 3). Using every fraction of the biomass, including the lignin, gives several revenue streams and leaves little waste, which improves both profitability and sustainability.




Fig. 3 Concept of an integrated residue biorefinery: ethanol, biogas, and heat and power from the same feedstock.

D. Decentralised, farm-based processing

Moving bulky straw and husk over long distances raises cost and emissions. Smaller biogas and bioethanol units placed near farms, run by farmer cooperatives or built as mobile processing units, would cut transport, create local jobs, supply energy within villages and give farmers a reason not to burn stubble.

E. Supply chain and storage

Biomass is bulky and seasonal, so steady production needs better logistics. Pelletisation and briquetting raise energy density and make transport cheaper, silage-style storage keeps residue usable through the year, digital marketplaces can match sellers and buyers, and contracts between farmers and industry give both sides price certainty.

F. Policy and financial support

Residue-based fuels cannot yet compete with fossil fuels without a supportive framework [4]. The measures most often proposed are ethanol blending mandates of E20 and beyond, carbon credits for biofuel producers, capital subsidies for biorefineries, guaranteed purchase prices for biomass and tax benefits for green fuels. Predictable support of this kind reduces risk for private investors.

G. Research and innovation

Further cost reduction depends on continued research: artificial intelligence for process control, new microbial strains, low-cost catalysts and hybrid biochemical–thermochemical conversion systems. Pilot plants that publish their real yields and costs would be particularly valuable, because they close the gap between laboratory estimates and commercial performance.

VIII. CURRENT STATUS IN INDIA

India has already moved a long way on ethanol blending. The 10% blending target was reached in 2022, five months ahead of schedule [5], and the government has since reported reaching 20% blending well before the original 2030 target [9]. Most of that ethanol comes from sugar and grain feedstocks, however, and second-generation ethanol is still at an early stage. The Panipat plant, dedicated in August 2022, was the first of its kind in the country, and several further second-generation plants are under development [5], [9]. The experience so far, including the feedstock-related shortfall noted above [10], supports the case made in this paper: the technology works, but reliable residue supply and process economics decide whether it scales.

© IARJSET This work is licensed under a Creative Commons Attribution 4.0 International License

IARJSET ISSN (O) 2393-8021, ISSN (P) 2394-1588

International Advanced Research Journal in Science, Engineering and Technology

Impact Factor 8.311 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 13, Issue 11, November 2026

DOI: 10.17148/IARJSET.2026.131174

IX. CONCLUSION

Agricultural residues could become one of the cheapest, cleanest and most dependable sources of fuel, but only if technology, logistics and policy advance together. The resource is large: even a collectable share of about 150 million tonnes a year could supply tens of billions of litres of ethanol or a substantial amount of biogas and power. Indicative life-cycle emissions are far below those of petrol and diesel, and the rural income and employment benefits are considerable.

The obstacles are equally clear: scattered and seasonal feedstock, costly pretreatment and enzymes, high capital cost and thin rural infrastructure. Operating plants have so far delivered lower yields than laboratory figures suggest, and on an energy basis the cost advantage over petrol is narrow. The strategies set out here, namely advanced pretreatment, improved enzymes and microbes, integrated biorefineries, farm-scale processing, stronger supply chains, supportive policy and continued research, address those obstacles directly. If they are pursued together, residue-based biofuels can move from a secondary option to a main pillar of sustainable energy systems.

Because many of the figures in this paper are indicative estimates, the next step should be site-specific techno-economic and life-cycle studies for Indian regions and crops, based on measured plant data.

REFERENCES

[1]. Pandey, A., Larroche, C., Soccol, C. R. and Dussap, S. C. 2019. *Biofuels: Alternative Feedstocks and Conversion Processes*, 2nd ed. Academic Press, Elsevier.

[2]. Sims, R., Mabee, W., Saddler, J. and Taylor, M. 2010. An overview of second generation biofuel technologies. *Bioresource Technology*, 101(6): 1570–1580.

[3]. McKendry, P. 2002. Energy production from biomass (Part 1): Overview of biomass. *Bioresource Technology*, 83: 37–46.

[4]. Ministry of New and Renewable Energy (MNRE), Government of India. *National Bio-Energy Mission and Biofuel Policy*. New Delhi, India.

[5]. Press Information Bureau, Government of India. 2022. India making significant progress in ethanol blending (factsheet), August 2022. https://static.pib.gov.in/WriteReadData/specificdocs/documents/2022/aug/doc202281188301.pdf

[6]. Ministry of New and Renewable Energy, Government of India. Reply to a question in the Lok Sabha on agricultural and agro-industrial residues. https://eparlib.nic.in/bitstream/123456789/680838/1/3365.pdf

[7]. From stubble to power: How India can tap the 28.45 GW potential of its surplus biomass residue. *Down To Earth* (reporting the National Biomass Atlas of India, SSS-NIBE/MNRE). https://www.downtoearth.org.in/air/from-stubble-to-power-how-india-can-tap-the-2845-gw-potential-of-its-surplus-biomass-residue

[8]. Vaish, S., Kaur, G., et al. 2022. Potential of agricultural biomass sources as projections of bio-briquettes in Indian context. *Sustainability*, 14(9): 5077.

[9]. Hardeep Singh Puri: India's ethanol drive achieves E20 early, eyes higher blends. *Devdiscourse*. https://www.devdiscourse.com/article/law-order/3534996-hardeep-singh-puri-indias-ethanol-drive-achieves-e20-early-eyes-higher-blends

[10]. Outlook Explains: Why India's ethanol revolution is sparking fresh food and water concerns. *Outlook India*. https://www.outlookindia.com/national/outlook-explains-why-indias-ethanol-revolution-is-sparking-fresh-food-and-water-concerns

[11]. Centre for Science and Environment. Factsheet on biomass-based power generation in India. New Delhi. https://cdn.cseindia.org/attachments/0.27588400_1581307484_factsheet-4.pdf

© IARJSET This work is licensed under a Creative Commons Attribution 4.0 International License